

D4C-Basic 210




Advance warning LED lights.

Single flash.

Wide range of settings.

Possibility of twilight function.

Works with 4 batteries 6V 4R25.

| | | |
|----------------------------------|---|----------------------|
| Model | D4C-Basic 210 | |
| Certification EN 12352 | L8H - L8M | |
| LED colour |  | |
| Operating time in hours | 4 batt. 7Ah | 300 |
| | 4 batt. 50Ah | 2000 |
| | 1 batt. 550Ah | 11500 (480 d) |
| LED light dimensions | Ø 210 x 85 mm | |
| Box dimensions | 150 x 165 x 235 mm | |



D4C-Basic 308




Advance warning LED lights.

Single flash.

Wide range of settings.

Possibility of twilight function.

Works with 4 batteries 6V 4R25.

| | | |
|-----------------------------|---|---------------------|
| Model | D4C-Basic 308 | |
| Approved EN 12352 | L9M | |
| LED colour |  | |
| Operating time in hours | 4 batt. 7Ah | 110 |
| | 4 batt. 50Ah | 800 |
| | 1 batt. 550Ah | 4400 (180 d) |
| LED light dimensions | Ø 333 x 110 mm | |
| Box dimensions | 150 x 165 x 235 mm | |

